

Technical Parameters	EGB7KJ-S2	EGB10KJ-S3	EGB14KJ-S4	EGB18KJ-S5	EGB21KJ-S6	EGB25KJ-S7	EGB28KJ-S8
BCU Module	BCU40035SH						
Number of BCU	1						
Battery Module	EGB4870SH (3.584 KWh / 70Ah, 51.2 VDC, 16S1P)						
Cell Type	LiFePO4						
Number of Modules	2	3	4	5	6	7	8
Rated Energy	7.16 KWh	10.75 KWh	14.33 KWh	17.92 KWh	21.50 KWh	25.08 KWh	28.66 KWh
Usable Energy	6.4 KWh	9.6 KWh	12.8 KWh	16.1 KWh	19.3 KWh	22.5 KWh	25.8 KWh
Continuous Current	35A/70A						
Max Output Power	3.5 KW	5.4 KW	7.1 KW	9.0 KW	10.8 KW	12.5 KW	14.3 KW
Peak Output Power	7KW/10S	10KW/10S	14KW/10S	17KW/10S	20KW/10S	25KW/10S	28KW/10S
Rated Voltage	102.4 VDC	153.6 VDC	204.8 VDC	256 VDC	307.2 VDC	358.4 VDC	409.6 VDC
Operating Voltage	96~112 VDC	144~168 VDC	192~224 VDC	240~280 VDC	288~ 336 VDC	336~392VDC	384~448 VDC
Dimension (mm)	600*260*621	600*260*806	600*260*991	600*260*1176	600*260*1361	600*260*1546	600*260*1731
Weight	90 kg	125 kg	160 kg	195 kg	230 kg	265 kg	300 kg
Communication	CAN /RS485						
Degree of Protection	IP65						
Mounting Method	Floor stand						
Operating Ambient	Charge: 0 C ~ 50 C / Discharge: -10 C ~ 50 C						
Humidity Range	0% to 95%(non-condensing)						
Cooling Method	Natural convection						
Warranty	10 years						